



23 KEY POINT ANNUAL SERVICE

1. Remove filter(s) and perform visual check of filter condition.
2. Check plumbing including pipe and heater unions and isolation valve connections for integrity and identify where possible any leaks present.
3. Check all worn or defective joint O-rings or gaskets.
4. Check jet body to hot tub shell joints for integrity where possible any leaks present.
5. Run all pumps to ensure satisfactory operation.
6. Check operation of system diverter valves, if fitted, and air control operation.
7. Check all jets for satisfactory operation – ensure they turn on & off if applicable.
8. Operate air blower, if fitted, and check satisfactory operation. Visually check that all the air injectors are allowing air through.
9. Check visually all equipment interconnecting wiring for integrity and insulation.
10. Check the control system and topside controls for operation of each function. A. Jet Booster pump(s), B. Circulation Pump (if fitted), C. Blower (if fitted), D. Filter Cycle setting (if available), E. Heating capability, F. Mode system.
11. Deep clean and sanitise the hot tub plumbing and pipe work system including pump wet end and heater tube.
12. Test the hot tub LED and lighting system.
13. Drain water from the hot tub and system.
14. Rinse spa thoroughly, drain and vacuum out majority of excess water from pipe work and jet bodies.
15. Wipe clean Hot Tub shell surface.
16. Refill with clean water to the required operating level.
17. Fit new or cleaned filters into the hot tub skim filter. (Filters used will be customers own pre-cleaned or new – only if purchased.)
18. Add pH+ or pH- to begin the correction of the pH level to attain a level of 7.2 to 7.4.
19. Add Sanitiser to achieve a level of 2-4ppm (mg/l) Chlorine or 3-5ppm (mg/l) Bromine. (see note)
20. Check operation of all Spa equipment from the control touch pad. Check operation of the heater and mode functions.
21. Vacuum skimmer and pump suction fittings.
22. Perform a test of the RCD if available and accessible.
23. Wipe down acrylic rim

NOTE: We will only treat a spa with a sanitiser recognised by the (HSE) Health & Safety Executive, Environmental Health or the (PHLS) Public Health Laboratory Service. Where the spa is treated with a non recognised sanitiser we will refill the spa with water and adjust the pH but we will not turn on spa. Recognised sanitisers are Bromine, Chlorine, Copper/Silver Ionisers (Nature2 etc.)

Terms and Conditions apply